Appendix 18

CODE



Mecklenburg County

"Code Enforcement"

INTERPRETATION

Code Volume Reference: Policy
Code Chapter Reference: Policy

Subject: Shell Requirements w/Core (mech.)

Effective Date: May 04, 2000

Prepared/Revision Date: March 19, 2001

POLICY:

CORE FACILITIES (Def.) =A space, which contains adequate plumbing fixtures for the floor, is directly accessible through direct openings or corridors from all tenant spaces, and is fully handicap accessible.

Multi-Story (Central HVAC):

Mechanical systems installed during the "SHELL w/CORE" phase shall consist of the supply/return duct, HVAC equipment, gas piping, bathroom exhaust, and water heater flue installed within the core and may include major trunk duct systems to tenant spaces. "SHELL w/CORE" shall not include branch duct systems to diffusers within tenant spaces.

Single Story:

Mechanical systems installed during the "SHELL w/CORE" phase is limited to the supply/return duct, HVAC equipment, gas piping, bathroom exhaust, and water heater flue installed within and limited to the CORE space. NO HVAC EQUIPMENT, FLUES, OR GAS PIPING ABOVE GRADE designed to serve any space/s other than the "CORE" will be allowed during the "SHELL w/CORE" phase of construction. The Mechanical Plans Reviewer or Mechanical Chief may allow exceptions on a case by case basis.

Exception: Buildings utilizing a central HVAC system <u>may</u> stub trunk duct into future tenant space/s and duct **SHALL** terminate at the VAV box or cap for future tenant upfit work/permit.

Prepared by: Consistency Team	David Deese & Vikki Stokes & Phil Edwards
Approved by:	Bawards

Philip B. Edwards, M/P Code Administrator